



SCANRANGER

Barcode Scanner

The barcode readers of Scanranger range offer advanced reading and decoding performance for a wide variety of applications: ideal for cash operations and for office automation applications. Ergonomic design optimized for a comfortable and firm grip even in case of long periods use. Sturdy, withstands a fall of 1.5 m. Beeper and LED help you to understand if the device is working.



ACCESSORIES

What is in the box:

- Device, USB-RJ45 cable, user manual, warranty card

CUSTOM 4CARE

Service programs for you
Discover Custom4Care

TECHNICAL SHEET

	1D	2D	
	SR100NM	SR200NM	SR300NM
Type	Corded		Wireless
Interface	HID USB/ USB COM Port emulation	HID USB/USB COM	HID USB/USB COM
1D Barcodes supported	All UPC/EAN/JAN, EAN 128 code, Code 39, Code 39 full ASCII, Code 32/Italian Pharmacy, Code 128, CODABAR/NW 7, Interleave 2 of 5, Industrial 2 of 5, Matrix 2 of 5, MSI/PLESSEY, Telepen, Code 93, Code 11, China Postage, GS1 DataBAR, GS1 Stacked codes	All UPC/EAN/JAN, EAN128 Code, Code 39, Code 39 Full ASCII, Code 128, CODABAR/NW7, Interleave 2 of 5, Industrial 2 of 5, Matrix 2 of 5, MSI/PLESSEY, Code 93, Code 11, China Postage, GS1 DataBar, GS1 Stacked codes	
2D Barcodes supported	-	PDF417, DataMatrix, QR Code	

COMMUNICATION

RF Standard	-	-	BT 4.0
Working distance	-	-	90 m (open environment)

OPTICAL

Optical sensor	2500 pixels	648 (H) x 488 (V) pixels	
Light source	RED LED (660 nm)	Aiming 610 nm red LED + white illumination LED	
Resolution	4 mil	5 mil	4 mil
Scan rate	100 scans/sec	60 fps	
Depth of field	10-390 mm	60 - 250 mm (13 mil)	74-203 mm (13 mil)
Indicator	Beeper and LED		
Print Contrast	-	Min. 30% @ UPC/EAN 100%	
Reading distance	-	up to 40 cm	

ELECTRICAL

Voltage	DC 5V
----------------	-------

ENVIRONMENT

Operating temperature	0 °C to 40 °C
Drop	1.5 m drops
IP Code	IP3X

PHYSICAL

Weight	190 g	-	-
Dimensions	82.53 mm (L) × 66.4 mm (W) × 162.08 mm (H)	-	-
Housing materials	ABS Plastic		

1D		2D	
SR100NM		SR200NM	SR300NM
BATTERY			
Battery type	-	-	Lithium-ion 3.7 V
Battery capacity	-	-	2.600 mAh good for 50.000 scans per charge
Charge	-	-	By USB power retrieving cable or cradle
<i>Product in the certification phase for the Brazilian Market</i>			

MODELS



994ED042600233
 BARCODE SCANNER
 SCANRANGER 1D CORDED
 SR100NM

995ED041800333
 BARCODE SCANNER
 SCANRANGER 2D CORDED
 SR200NM

995ED041700A33
 BARCODE SCANNER
 SCANRANGER 2D WIRELESS
 SR300NM

995ED041600A33
 BARCODE SCANNER
 SCANRANGER 2D WIRELESS
 CRADLE SR300NM-CR

CUSTOM SPA - Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: T180W10

The technical data on this website are not binding and may be changed without advanced notice.
 Last update: 16 November 2020