



## Features

### Powerful Performance

Fast and smooth performance is at your fingertips with the M10. It comes equipped with Android 9.0 and is powered by a 2.0GHZ octa-core processor.

### Sleek Design

At only 12.6mm thick, the M10 is ready to go where you go. Whether holding it in your pocket or hand, you are sure to be comfortable.

### Antimicrobial Casing

With healthcare in mind, the M10 features an antimicrobial casing that is built to resist even the harshest cleaning agents.

### Long Battery Life

With a 4800mAh battery and a low power design, the M10 is ready for a full day of use. Equipped with a Type-C port, the M10 also supports fast charging.

### Versatile Connectivity

With dual band 802.11 a/b/g/n/ac, WiFi and 4G support, the M10 stays connected both indoors or in the field. The dual SIM option allows you to stay connected with your chosen provider.

## Application Scenarios



# M10 technical specifications

<b>Performance</b>	Operating System	Android 9.0
	Processor	2.0 GHz octa-core 64-bit processor
	Memory RAM	4GB
	Memory Flash	64GB
	Memory Storage Expansion (Max.)	Micro SD card (max. 128GB)
<b>Data capture</b>	1D	Code128, UCC/EAN-128, AIM-128, EAN-8, JAN-8, EAN-13, ISBN/ISSN, UPC-E, UPC-A, Interleaved 2/5, ITF-6, ITF-14, Deutsche 14, Deutsche 12, COOP 25, Matrix2/5, Industrial 2/5, Standard 25, Code 39, Codabar/NW7, Code 93, Code 11, Plessey, MSI/Plessey, GS1, Databar, etc.
	2D	PDF417, QR Code, Data Matrix, Aztec, etc.
<b>Physical</b>	Dimensions (mm)	157x76.3x12.6mm
	Weight	231g (including battery)
	Display	5.7" (1440x720)
	Touch panel	18:9 multi-point capacitive touch screen
	Keypad	5 keys (side keys included)
	Interfaces	Type-C 2.0 OTG
	Battery Type	3.8 V, 4800mAh
	Notifications	Vibrator, speaker and multi-color LEDs
	Power Supply Input	AC110 ~ 220V, 50~60Hz
	Power Supply Output	DC5V/7V/9V, 1.67A
	Audio	Microphone, speaker, Type-C earphone, FM
	Audio Jack	Type-C earphone
	Expansion Slot	MicroSD (max 128GB) slot
	Camera	Front Camera: 2 megapixels, fixed focus; Rear camera: 13 megapixels, auto focus, with LED flashlight
SIM	Nano+Nano or Nano+TF	
<b>Environmental</b>	Operating Temperature	-20°C to 50°C (14°F to 122°F)
	Storage Temperature	-30°C to 60°C (-22°F to 140°F)
	Humidity	5% to 95% (non-condensing)
	Electro Static Discharge (ESD)	±12kV (air discharge); ±8kV (direct discharge)
	Drop	1.22m drops to concrete (MIL-STD-810G), 1.5m drops to concrete (GB/T 2423.8-1995 Part 2)
	Sealing	IP67
<b>Wireless</b>	WWAN Radio	2G: GSM/GPRS/EDGE (850/900/1800/1900MHz); 3G: WCDMA (B1, B2, B5, B8); CDMA 1X/EV-DO (BC0, BC1); 4G: TD-LTE (B41); FDD-LTE (B1, B2, B3, B4, B7, B12, B13, B17)
	WLAN Radio	IEEE 802.11 a/b/g/n/ac, 2.4GHz and 5GHz
	WPAN Radio	Bluetooth 5.0
	RFID	13.56MHz RFID: ISO14443A/B, ISO15693, ISO18000-3, MIFARE, FeliCa RF, Kovio, NFC Forum Type 1-4 tags
	GPS	GPS, Beidou, GLONASS
<b>Accessories</b>	Optional	4-slot charging cradle
	Standard	AC adapter, cable, single slot charging cradle
<b>Device Management</b>	Software	Ndevor by Newland (MDM)
<b>Certifications</b>	Certifications	Antimicrobial housing: Escherichia coli, Staphylococcus aureus