

PT60 Narvalo

Windows Mobile Computer





Features

Megapixel Camera.

The PT60 Narvalo is equipped with a megapixel camera that scans virtually any 1D and 2D barcode with impressive speed and ease. Built to work with Windows CE, you can be sure the device fits your operations perfectly.

Uninterrupted Productivity.

Armed with a 3,800 mAh battery, the PT60 Narvalo lasts an average of 10 hours. For scan intensive workdays, a cradle with spare battery charging slot can be used to ensure a full charge is always on hand.

• Stay Connected.

The PT60 Narvalo is equipped with Bluetooth and WiFi (802.11b/g/n, 2.4 Ghz) that supports up to 54Mbps.

Application Scenarios

Transport and Logistics (Warehouse, Backoffice), Retail (Warehouse, Backoffice, Store), Manufacturing (Operational Data Collection) and Healthcare (Patient Care, Laboratory and pharmacy).

Less Weight, more Comfort.

At only 303g (including battery), this mobile computer brings all day comfort to your operations. Its physical keyboard combined with a crystal clear 3.7 inch touch screen allows workers to navigate the device with ease.

• Effortless out of the Box Experience.

Take the PT60 Narvalo out of the box and get started right away. The device comes ready to use and configuration is quick and simple, minimizing the time needed to set up the devices.





PT60 Narvalo

Windows Mobile Computer

Performance	Image Sensor		1280 * 960 CMOS Mega Pixel
	Processor		Marvell XScale PXA310, 806MHz CPU
	Operating System		Microsoft Windows CE.NET 6.0
	Memory		256MB RAM
			128MB ROM
			4GB flash memory for user storage
	Interface		Micro USB 2.0, Battery charging over USB supported
Physical	Dimensions		166(L) ×73(W) ×26(H) mm
	Weight		303g (including battery)
	Display		3.7" WVGA with backlight TFT touch screen
	Keypad		33 keys (side keys included) with backlight
	Notification		Vibrator, speaker and multi-color LEDs
	Battery	Main	3.7V, 3800mAh rechargeable Li-Polymer battery
		Backup	3.7V, 150mAh rechargeable Li-Polymer battery (supports 50-hour data backup)
	Expected Battery Life		10 hours (1 scan per second)
	Expansion		MicroSD card slot (max. 32GB)
	AC Adapter		Output: DC5V, 1.5A Input: AC100~240V, 50~60Hz
Environmental	Operating Temperature	!	-10°C to 50°C (-14°F to 122°F)
	Storage Temperature		-20°C to 60°C (-4°F to 140°F)
	Humidity		5% to 95% (non-condensing)
	Static Discharge		±15 kV (Air discharge), ±8 kV (Direct discharge)
	Drop		1.2m
	Sealing		IP54
Barcode Scanning	1D Barcode	Laser (≥4mil) CCD (≥4mil)	Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ISBN/ISSN, Code 93, etc.
	2D Barcode	CMOS(≥5mil)	All major 1D symbologies, PDF417, QR Code, Data Matrix, Maxicode, Aztec, etc.
Wireless	WLAN RADIO		IEEE 802.11 b/g/n, security supports EAP, WEP, WPA, WPA2
	WPAN RADIO		Bluetooth Class II V2.0
Certifications			FCC Part15 Class B, CE EMC Class B, CCC
Accessories			Cradle, battery, AC adapter, USB cable, stylus
*Specifications are sub	piect to change without notice		

^{*}Specifications are subject to change without notice.

Newland EMEA HQ +31 (0) 345 87 00 33 info@newland-id.com

Newland D-A-CH +49 (0) 6182 82916-16 info@newland-id.de

Newland France +31 (0) 345 87 00 33 france@newland-id.com Newland Benelux +31 (0) 345 87 00 33 benelux@newland-id.com

Newland Ibérica +34 (0) 93 303 74 66 info@newland-id.es

Newland Italy +39 (0) 342 056 2227 italy@newland-id.com Newland Nordic & Baltic +46 (0) 708 847 767 nordic@newland-id.com

Newland UK +44 (0) 1442 212 020 sales@newland-id.co.uk

Newland Russia +31 (0) 345 87 00 33 russia@newland-id.com Newland South Africa +27 (0) 11 553 8010 info@newland-id.co.za

Newland Middle East +31 (0) 345 87 00 33 middleeast@newland-id.com

Newland Turkey & Iran +90 (0) 544 538 40 49 turkey@newland-id.com iran@newland-id.com