













UHF RFID reader



Gun Grip



Charging cradle for gun grip

RETHINK your idea of a rugged enterprise mobile computer with the **SLEEK DESIGN** of the EA500P(Plus)

The unitech EA500P (Plus) Android 8 comes with the Google GMS license. It is a rugged 5" mobile enterprise computer within a compact stylish design. The EA500P (Plus) combines strong features with powerful data collection. It provides convenient connectivity (with fast roaming), reading capabilities and enhances the service level for a variety of vertical applications within the retail, hospitality, healthcare and field service sectors.





Dual-Sim

The Unitech EA500P (Plus) supports Dual-Sim. A great way to manages business and personal numbers within the same device or you can add a local data plan while traveling outside of your home country or region.



Allrouder

Thanks to POGO pins and USB-C connerctor on the bottom side, the EA500P (Plus) has limitless scalability options for future accessories such as gun grip and docking stations.



Compact design enterprise format

EA500P (Plus) is one of the most flexible and sleek enterprise mobile computer with a weight of only 210g.



Choose your engine

The EA500P (Plus) gives your workforce the technology it needs to take your business to the next level. The EA500P (Plus) is available with a Basic 2D imager or Premium 2D imager.

Operation System

CPU 1.4GHz, Qualcomm 8940 octa core 64 bits processor

Memory RAM 2GB/4GB optional ROM 16GB/64GB optional OS Android 8 with GMS

Google Enterprise Device certified

SIM Dual Sim
Languages Multi-language

Others Input Chinese/ English, supports handwriting

and soft keyboard.

Display

5.0 inch TFT-LCD HD (720 x 1280) color screen, 300nits, Gorilla Glass 3. Ultra sensitive capacitive touch screen, compatible with gloves and supports wet resistance.

Camera/Photos/Video

2MP front camera

13MP rear camera with LED flash and auto-focus function

Indicator

LED's and vibration

Communication

USB Type C
OTG Yes, over USB Type C

POGO PIN Charging via cradle and USB client WLAN IEEE 802.11a/b/g/n/ac/d/e/f/h/i/k/v/w/r

IPV4, IPv6.

FAST ROAMING
Bluetooth®
WWAN

PMKID caching, 802.11r, OKC
Bluetooth® 4.2 + BR/EDR + BLE
Global brands with dual SIM Slot

4G: FDD-LTE (B1/B2/B3/B4/B5/B7/B8/B20/

B28A/B28B)

3G: WCDMA(B1/B2/B5/B8) (2100, 1900,850, 900 MHz) 2G: GSM/EDGE/GPRS

(850, 900, 1800, 1900 MHz) GPS GPS, AGPS, BeiDou, GLONASS

Sensors Acceleration, motion, proximity sensor, light sensor,

G-sensor, digital compass (E-compass), pressure sensor, gyroscope and height meter

Vibration 5Hz to 2KHz,60 minute duration per axis, 3 axis

WiFi Security

WLAN Security: 802.1x(EAP): EAP-TLS, EAP-TTLS, PEAP-MSCHAPv2,

PEAP-TLS, PEAP-GTC, PWD, SIM, AKA

Encryption: WEP, WPA/WPA2-PSK

Buttons

5 keys- Programmable function button; dual dedicated scan buttons; volume up/down buttons; on/off button

EA500P(PLUS)

v1.0 Specifications

Software Support















SOTI TeamViewer airwatch Zello

Data capture
2D IMAGER

BASIC 2D: Zebra SE2700

Suppor t all major 1D and 2D barcodes

PREMIUM 2D: Honeywell N6603 engine.

White illumination High Visibility Laser Aimer

Fast scan speed

Ultra-fast motion tolerance up to 5 meters p/s

Supports color barcodes

Supports poorly printed barcodes Supports 1D, 2D and OCR

Symbology/X-Dim Typical Range*

 100% U.P.C
 46 mm - 419 mm

 5 mil Code 39
 64 mm - 163 mm

 10 mil Code 39
 28 mm - 338 mm

 6.7 mm PDF417
 46 mm - 185 mm

 10 mil Data Matrix
 53 mm - 203 mm

Resolution linear barcodes: 0.127 mm Resolution 2D matrix codes: 0.169 mm

HF/NFC Frequency 13.56Mhz

Support: ISO14443A/B, ISO15693 standard,

Supports NFC

Power Source

Main battery Rechargeable and Changeable (Non-swappable)

3.8V 4000mAh (typical) 3.8V 3800mAh (minimum)

Operation time 10-12 hours

(depending on the specific environment)

RTC battery Real time clock battery

Audio

Microphone, speaker and 3.5mm audio jack. Support noise cancellation, PPT headset support, cellular circuit switch voice.

Enclosure

Dimension 155.8 mm x 76.2 mm x 13.5 mm

Weight 210g with battery

Environmental

Operating temperature -10°C to +50°C Storage temperature -20°C to +70°C Charging Temperature 0°C to 40°C

Relative Humidity 5% ~ 95% (non-condensing)
Drop Specification 1.5m drop to concrete at room temperature per MIL-STD810G

Sealing IP0

Tumble 1.0m tumble for 200 cycles and 400 times

ESD 8K / 15KV

Device supported MDM

SOTI, AirWatch, 42Gears and MoboLink

Regulatory Approvals

CE, RED, NCC, BSMI, CCC, VCCI, FCC

Accessories

USB type C cable / adaptor 1-slot charging cradle
Power adaptor 6-slot charging cradle
Sylus Gun gripHandstrap
Glass Screen protector Charging cradle for gun grip
Vehicle cradle RP100 UHF/RFID Reader

Screw mount for vehicle cradle Suction mount for vehicle cradle

Heavy Duty suction mount for vehicle cradle



Unitech Europe
Tilburg, The Netherlands • Tel.: +31 (0)13 460 9292 • Email: Info@eu.ute.com • Website: http://eu.ute.com