



HT510

Rugged Handheld Terminal

One-Handed Operation. Double Efficiency



Unitech HT510 is the ideal data collector for operators to easily navigate with one hand. It offers a large 3.5" display and easily operable large keys design. Along with optional barcode & RFID decoders, operators can collect data and utilize HT510 with ease, significantly increasing work efficiency. HT510 runs on Microsoft WinCE platform, making it simple for developers to develop software and for operators to integrate and manage data across all systems ensuring all information is aligned and accurate; effectively saving cost and time.

Designed for harsh environments, HT510's rugged design withstand multiple drops to concrete from 1.5 meters (free fall on 6 sides) and equipped with IP65 environmental seal against water and dust. HT510 offers various handy accessories to effectively increasing its ease of operation and overall productivity.

■ Features

- Windows CE 6.0 Pro Operating System
- Large 3.5" Display, Large Keys; Easily Operable with One Hand
- IP 65 Rating & Withstand Multiple Drops from 1.5 Meters
- Integrated Bluetooth, WLAN, WWAN 3G Wirelss Technology
- Offers Multiple Decoder Options to Meet Your Various Requirements (Optional 1D/2D/UHF)

System Features

OS	Windows CE 6.0 Pro
CPU	1GHz
Memory	4GB ROM / 512MB RAM
Display	3.5" QVGA (240x 320) Resistive Colour Touch Screen with Adjust- able Backlight
Language Support	English & Chinese Versions

Keys

32 keys ; Large Numeric, Functional & Directional Keys

Communication

Camera	5M Pixels Camera with Flash Light and Auto-Focus
External Storage	Supports MicroSD up to 64GB
USB	USB 1.1, Mini USB & Rugged POGO-Pin
WLAN	IEEE 802.11b/g/n , Supports IEEE 802.1X Security
Bluetooth	Bluetooth 2.1+EDR
WWAN(Optional)	GSM: 900 , 1800MHz WCDMA: 900 , 2100MHz

Decoder

Barcode Reader	Optional 1D Laser & 2D Imager
RFID	Optional ISO18000-6B & C UHF Decoder

Power Source

Main Battery	3.8V 4500mAh
--------------	--------------

Enclosure

Dimension	L192 x W73.8 x H30 mm
Weight	385g (Including Battery)

Symbologies

1D Laser	UPC/EAN, Bookland EAN, UCC Coupon Code, ISSN EAN, Code 128, GS1-128, ISBT128, Code39, Trioptic Code39, Code32, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Codabar, MSI, Matrix 2 of 5, Inverse 1D, GS 1 DataBar, Compos- ite Codes.etc.
2D Imager	PDF417, MicroPDF417, Data Matrix, Data Matrix Inverse, Maxicode, QR Code, MicroQR, QR Inverse, Aztec, Aztec Inverse, Han Xin, Han Xin Inverse, etc.

Environmental

Operating Temperature	-10°C~50°C
Storage Temperature	-20°C~70°C
Relative Humidity	5%~95% (non-condensing)
Environmental Sealing	IP65
Drop Test to Concrete	1.5 meters

Developer Tool

Windows CE 6.0 SDK

Audio

Built-In Microphone, Speaker & Audio Jack

Regulation Approvals

NCC, BSMI

Optional Accessories

USB Cradle, USB Cable, 4-Slot Battery Slot, Battery,
Holster, Stylus Pen, Gungrip

Headquarters

Taipei, Taiwan
<http://www.ute.com> e-mail: info@hq.ute.com

Unitech America

Los Angeles
<http://us.ute.com> e-mail: info@us.ute.com
<http://can.ute.com> info@can.ute.com
Mexico
<http://latin.ute.com> e-mail: info@latin.ute.com

Unitech Asia Pacific & Middle East

Taipei
<http://apac.ute.com> info@apac.ute.com / info@india.ute.com
<http://mideast.ute.com> info@mideast.ute.com

Unitech Europe

Tilburg / Netherlands
<http://eu.ute.com> e-mail: info@eu.ute.com

Unitech Japan

Tokyo
<http://jp.ute.com> e-mail: info@jp.ute.com

Unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen
<http://cn.ute.com> info@cn.ute.com
Taipei <http://tw.ute.com> info@tw.ute.com

